ROLLCO LINEAR SOLUTIONS YOUR WAY

Metal-Plastic Cap

The top of the cap is made of stainless steel and prevents dirt or scrap from piling up in the bolt hole, which may affect the end seal function.

The lower part of the cap is made of plastic and can be installed directly on the standard rail. There is no need to conduct other fine slot milling for bolt-hole.

The bolt-hole chamfer for standard rail is C0.2 mm. A nonbolt-hole chamfer rail is available on request for absolutely dust-proof applications. Please contact us for more information.

The cap is designed with supporting block to prop up the cap, fix the screw stably and prevent it from sinking.






Cap before hammering (Plastic support)

Plastic support after hammering (8 supporting block become deformed, and fit with the screw.)






General Data

Designation	Compatible with Screw Type		
MPC-A4	AR15, WRC21/15, WRC27/20	M4	
MPC-A5	AR20	M5	
MPC-A6	AR25 M6		
MPC-A8	AR30 , AR35	M8	
MPC-A12	AR45 M12		
MPC-A14	AR55	M14	

Rollco AB • Box 22234 • 250 24 Helsingborg • Sweden • Phone +46 42 15 00 40 • info@rollco.se

Dimensions



Designation	н	С	D
MPC-A4	1.7	2.0	7.7
MPC-A5	3.4	4.0	9.7
MPC-A6	2.9	3.5	11.3
MPC-A8	3.9	4.5	14.3
MPC-A12	5.0	5.6	20.4
MPC-A14	6.0	6.5	24.4

Rollco AB • Box 22234 • 250 24 Helsingborg • Sweden • Phone +46 42 15 00 40 • info@rollco.se Every care has been taken to ensure the accuracy of the information in this document, but we take no liability for any errors or omissions. We reserve the right to make changes without prior notice.