

XTR---.0300

- Combined – adjustable with insert washer
- Extra sustainable
- Extra exact
- Extra strong
- Extra long-lasting
- Adjustment of dimension A by using a shim

Use profile XUP---.0700

Fixing square element BQ---.1000

Rectangular fixing element BR---.1100

Note! System Load Capacity refers to capacity of both rail and bearing. Dynamic Load Capacity refers to bearing.

Dimensions in mm.

Roller Type: Heavy

Sizes Available: 60; 70; 80; 90; 110; 120; 150





General Data

FA = System Load Capacity Axial
 FR = System Load Capacity Radial
 Ca = Dynamic Load Capacity Axial
 C = Dynamic Load Capacity Radial



| Designation | System Load Capacity Radial (N) | System Load Capacity Axial (N) | Dynamic Load Capacity Axial (N) | Dynamic Load Capacity Radial (N) | Profile |
|-------------|---------------------------------|--------------------------------|---------------------------------|----------------------------------|-----------------|
| XTR060.0300 | 15390 | 3800 | 8000 | 31000 | XUP-- -.0700 |
| XTR070.0300 | 16430 | 4100 | 13000 | 45500 | XUP-- -.0700 |
| XTR080.0300 | 18210 | 6500 | 14000 | 48000 | XUP-- -.0700 |
| XTR090.0300 | 31680 | 6600 | 15000 | 68000 | XUP-- -.0700 |
| XTR110.0300 | 34850 | 11500 | 31000 | 81000 | XUP-- -.0700 |
| XTR120.0300 | 47430 | 12700 | 31000 | 110000 | XUP-- -.0700 |
| XTR150.0300 | 82190 | 22600 | 68000 | 151000 | XUP-- -.0700 |

