LSG

Dimensions in mm.

Material: Steel (black cataphoresis) or stainless steel AISI 316





Every care has been taken to ensure the accuracy of the information in this document, but we take no liability for any errors or omissions. We reserve the right to make changes without prior notice.


General Data


Designation	Compatible with	Material	Fmax (N)	Mass (kg)
LSG 32 - 8129	PNCE 32	Steel (black cataphoresis)	F PNCE	0.18
LSG 32 CR - 69071	PNCE 32	Stainless steel AISI 316	F PNCE	0.18
LSG 40 - 8130	PNCE 40	Steel (black cataphoresis)	F PNCE	0.27
LSG 40 CR - 69072	PNCE 40	Stainless steel AISI 316	F PNCE	0.27
LSG 50 - 8131	PNCE 50	Steel (black cataphoresis)	F PNCE	0.46
LSG 50 CR - 69073	PNCE 50	Stainless steel AISI 316	F PNCE	0.46
LSG 63 - 8132	PNCE 63	Steel (black cataphoresis)	F PNCE	0.55
LSG 63 CR - 69069	PNCE 63	Stainless steel AISI 316	F PNCE	0.55
LSG 80 - 8133	PNCE 80	Steel (black cataphoresis)	F PNCE	0.97
LSG 80 CR - 83089	PNCE 80	Stainless steel AISI 316	F PNCE	0.97
LSG 100 - 8127	PNCE 100	Steel (black cataphoresis)	F PNCE	1.33
LSG 100 CR - 83090	PNCE 100	Stainless steel AISI 316	F PNCE	1.33

Dimensions









Designation	L1	L2	L3	L4	L5	L6	L7	L8	L9
LSG 32 - 8129	51	38	14	32 (JS 15)	22	10.5	8.5	18	31
LSG 32 CR - 69071	51	38	14	32 (JS 15)	22	10.5	8.5	18	31
LSG 40 - 8130	54	41	16	36 (JS 15)	22	10.5	8.5	18	31
LSG 40 CR - 69072	54	41	16	36 (JS 15)	22	10.5	8.5	18	31
LSG 50 - 8131	65	50	21	45 (JS 15)	26	12	8.5	22	35
LSG 50 CR - 69073	65	50	21	45 (JS 15)	26	12	8.5	22	35
LSG 63 - 8132	67	52	21	50 (JS 15)	33	15	10.5	30	45
LSG 63 CR - 69069	67	52	21	50 (JS 15)	33	15	10.5	30	45
LSG 80 - 8133	86	66	25	63 (JS 15)	38	15	10.5	35	50
LSG 80 CR - 83089	86	66	25	63 (JS 15)	38	15	10.5	35	50
LSG 100 - 8127	96	76	25	71 (JS 15)	49	18	11.5	40	60
LSG 100 CR - 83090	96	76	25	71 (JS 15)	49	18	11.5	40	60

Designation	L10	L11	D1	D2	D3	R1	R2
LSG 32 - 8129	21 (JS 15)	3	Ø 10 (H7)	Ø 6.6 (H13)	Ø 20 (H13)	15	5.5 (H13)
LSG 32 CR - 69071	21 (JS 15)	3	Ø 10 (H7)	Ø 6.6 (H13)	Ø 20 (H13)	15	5.5 (H13)
LSG 40 - 8130	24 (JS 15)	3	Ø 12 (H7)	Ø 6.6 (H13)	Ø 20 (H13)	18	5.5 (H13)

Every care has been taken to ensure the accuracy of the information in this document, but we take no liability for any errors or omissions. We reserve the right to make changes without prior notice.

Designation	L10	L11	D1	D2	D3	R1	R2
LSG 40 CR - 69072	24 (JS 15)	3	Ø 12 (H7)	Ø 6.6 (H13)	Ø 20 (H13)	18	5.5 (H13)
LSG 50 - 8131	33 (JS 15)	3	Ø 16 (H7)	Ø 9 (H13)	Ø 20 (H13)	20	7.5 (H13)
LSG 50 CR - 69073	33 (JS 15)	3	Ø 16 (H7)	Ø 9 (H13)	Ø 20 (H13)	20	7.5 (H13)
LSG 63 - 8132	37 (JS 15)	3	Ø 16 (H7)	Ø 9 (H13)	Ø 20 (H13)	23	7.5 (H13)
LSG 63 CR - 69069	37 (JS 15)	3	Ø 16 (H7)	Ø 9 (H13)	Ø 20 (H13)	23	7.5 (H13)
LSG 80 - 8133	47 (JS 15)	3	Ø 20 (H7)	Ø 11 (H13)	Ø 20 (H13)	27	9 (H13)
LSG 80 CR - 83089	47 (JS 15)	3	Ø 20 (H7)	Ø 11 (H13)	Ø 20 (H13)	27	9 (H13)
LSG 100 - 8127	55 (JS 15)	3	Ø 20 (H7)	Ø 11 (H13)	Ø 20 (H13)	30	9 (H13)
LSG 100 CR - 83090	55 (JS 15)	3	Ø 20 (H7)	Ø 11 (H13)	Ø 20 (H13)	30	9 (H13)

Every care has been taken to ensure the accuracy of the information in this document, but we take no liability for any errors or omissions. We reserve the right to make changes without prior notice.